

# SCHROEFASVET



RESISTANCE  
WATER



## CLASSIFICATION

DIN 51502

K2K-30

## PRODUCT DESCRIPTION

**Schroefasvet** is a lithium thickened lubricating grease based on mineral oil.

**Schroefasvet** is suitable for heavily loaded industrial applications where water wash is problematic. The product is also suitable for heavy-duty vehicles working outdoors in wet and dirty conditions.

The thickener, together with the base oil, makes the product suitable for the lubrication of slow moving and heavily loaded bearings.

- Excellent water resistance
- Good mechanical stability
- Wide range of applications

## TYPICAL TECHNICAL DATA

Thickener		Lithium
Base oil		Mineral Oil
Colour	Visual	Brown
NLGI Grade	ASTM D217	2
Dropping point	IP 396	>180°C
Base oil viscosity at 40°C	ISO 12058	90-120 mm <sup>2</sup> /s
Base oil viscosity at 100°C	ISO 12058	12 mm <sup>2</sup> /s
4-Ball weld load	DIN 51350:4	2000 N
Temperature range		-30°C to +120°C Max +130°C

**OML B.V.**

Postbus 342

4940 AH Raamsdonksveer

[E\\_order@omlbv.nl](mailto:E_order@omlbv.nl)

[E\\_info@omlbv.nl](mailto:E_info@omlbv.nl)

[www.omlbv.nl](http://www.omlbv.nl)

Tel +31(0)162 51 16 85